



NASA SBIR 2009 Phase I Solicitation

S1.03 Passive Microwave Technologies

Lead Center: GSFC

Participating Center(s): JPL

NASA employs passive microwave and millimeter-wave instruments for a wide range of remote sensing applications from measurements of the Earth's surface and atmosphere (http://www.nap.edu/catalog.php?record_id=11820) to cosmic background emission. Proposals are sought for the development of innovative technology to support future science and exploration missions employing 450 MHz to 5 THz sensors. Technology innovations should either enhance measurement capabilities (e.g., improve spatial, temporal, or spectral resolution, or improve calibration accuracy) or ease implementation in spaceborne missions (e.g., reduce size, weight, or power, improve reliability, or lower cost). While other concepts will be entertained, specific technology innovations of interest are listed below for missions including decadal survey missions (<http://www.nap.edu/catalog/11820.html>) such as PATH, SCLP, and GACM and the Beyond Einstein Inflation Probe (Inflation Probe (cosmic microwave background, <http://universe.nasa.gov/program/probes/inflation.html>)).

- Low power >200 Mb/s 1-bit A/D converters and cross-correlators for microwave interferometers. Earth Science Decadal survey missions which apply: PATH, SCLP.
- Automated assembly of 180 GHz direct conversion I-Q receiver modules. This technology applies to both the Beyond Einstein Inflation probe and the Decadal Survey PATH concept.
- Low DC power spectrometer (channelizer) covering >500 MHz with 125 kHz resolution for planetary radiometer missions and covering 4 GHz with 1 MHz resolution for Earth observing missions. Also RFI mitigation approaches employing channelizers for broad band radiometers. Earth Science Decadal Survey mission which applies: GACM
- RF (GHz to THz) MEMS switches with low insertion loss (18 dB), capable of switching with speeds of >100 Hz at cryogenic temperatures (below 10 K) for 10^8 or more cycles. Technology applies to Beyond Einstein Probe.
- High emissivity (>40 dB return loss) surfaces/structures for use as onboard calibration targets that will reduce the weight of aluminum core targets, while reliably improving the uniformity and knowledge of the calibration target temperature. Earth Science Decadal survey missions which apply: SCLP and PATH.
- MMIC Low Noise Amplifiers (LNA). Room temperature LNAs for 165 to 193 GHz with low 1/f noise, and a noise figure of 6.0 dB or better; and cryogenic LNAs for 180 to 270 GHz with noise temperatures of less

than 150K. Earth Science Decadal Survey missions that apply: PATH and GACM.

- Low loss, low RF power waveguide SPDT diode switches and active noise sources for frequencies above 90 GHz to support calibration of SWOT and other atmospheric temperature and humidity measurements.
- Broad band 180 - 270 GHz radomes for aircraft borne submillimeter remote sensing instruments.

Proposals should show an understanding of one or more relevant science needs, and present a feasible plan to fully develop a technology and infuse it into a NASA program.