



## NASA SBIR 2015 Phase I Solicitation

### H2.02 Nuclear Thermal Propulsion (NTP)

Lead Center: MSFC

Participating Center(s): GRC, SSC

Solid core NTP has been identified as an advanced propulsion concept which could provide the fastest trip times with fewer SLS launches than other propulsion concepts for human missions to Mars over a variety of mission years. The current NASA Strategic Space Technology Investment Plan states NTP is a high priority technology needed for future human exploration of Mars. NTP had major technical work done between 1955-1973 as part of the Rover and Nuclear Engine for Rocket Vehicle Application (NERVA) programs. A few other NTP programs followed including the Space Nuclear Thermal Propulsion (SNTP) program in the early 1990's. The NTP concept is similar to a liquid chemical propulsion system, except instead of combustion in the thrust chamber, a monopropellant is heated with a fission reactor in the thrust chamber. In addition, the engine components and surrounding structures are exposed to a radiation environment formed by the reactor during operation.

This solicitation will examine a range of modern technologies associated with NTP using solid core nuclear fission reactors and technologies needed to ground test the engine system and components. The engines are pump fed ~15,000-35,000 lbf with a specific impulse goal of 900 seconds (using hydrogen), and are used individually or in clusters for the spacecraft's primary propulsion system. The NTP can have multiple start-ups (>4) with cumulative run time >100 minutes in a single mission, which can last a few years. The Rover/NERVA program ground tested a variety of engine sizes, for a variety of burn durations and start-ups with the engine exhaust released to the open air. Current regulations require exhaust filtering of any radioactive noble gases and particulates released to stay within the current environmental regulations. The NTP primary test requirements can have multiple start-ups (>8) with the longest single burn time ~50 minutes.

Specific engine technologies of interest to meet the proposed requirements include:

- High temperature (> 2600K), low burn-up composite, carbide, and/or ceramic-metallic (cermet) based nuclear fuels with improved coatings and/or claddings to maximize hydrogen propellant heating and to reduce fission product gas release and particulates into the engine's exhaust stream.
- Long life, lightweight, reliable turbopump modeling, designs and technologies including seals, bearing and fluid system components. Throttle ability is also considered. Zero net positive suction head (NPSH) hydrogen inducers have been demonstrated that can ingest 20-30% vapor by volume. The goal would be to develop inducers that can ingest 55% vapor by volume for up to 8 hours with less than 10 percent head fall off at the design point. Develop the capability to model (predict) turbopump cavitation dynamics. This includes first order rotating and alternating cavitation (1.1X –2X) and higher (6X-10X) order cavitation dynamics.
- High temperature and cryogenic radiation tolerant instrumentation and avionics for engine health monitoring. Non-invasive designs for measuring neutron flux (outside of reactor), chamber temperature, operating pressure, and liquid hydrogen propellant flow rates over wide range of temperatures are desired. Sensors need to operate for months/years instead of hours. Robonaut type inspections for prototype flight

---

test considered.

- Concepts to cooldown the reactor decay heat after shutdown to minimize the amount of open cycle propellant used in each engine shutdown. Depending on the engine run time for a single burn, cool down time can take many hours.
- Low risk reactor design features which allow more criticality control flexibility during burns beyond the reactor circumferential rotating control drums, and/or provide nuclear safety for ground processing, launch, and possible launch aborts.

Specific ground test technologies of interest to meet the proposed requirements include:

- Effluent scrubber technologies for efficient filtering and management of high temperature, high flow hydrogen exhausts. Specific interests include:
  - Filtering of radioactive particles and debris from exhaust stream having an efficiency rating greater than 99.9%.
  - Removal of radioactive halogens, noble gases and vapor phase contaminants from a high flow exhaust stream with an efficiency rating greater than 99.5%.
- Technologies providing a low power nuclear furnace to test a variety of fuel elements at conditions replicating a full scale NTP engine.

For all above technologies, research should be conducted to demonstrate technical feasibility during Phase I and show a path towards Phase II hardware/software demonstration with delivery of a demonstration unit or software package for NASA testing at the completion of the Phase II contract.

*Phase I Deliverables* - Feasibility study, including simulations and measurements, proving the proposed approach to develop a given product (TRL 2-3). Verification matrix of measurements to be performed at the end of Phase II, along with specific quantitative pass-fail ranges for each quantity listed.

*Phase II Deliverables* - Working engineering model of proposed product, along with full report of component and/or breadboard validation measurements, including populated verification matrix from Phase I (TRL 4-5). Opportunities and plans should also be identified and summarized for potential commercialization.