



NASA SBIR 2016 Phase I Solicitation

H4.03 EVA Space Suit Power, Avionics, and Software Systems

Lead Center: JSC

Participating Center(s): GRC

Space suit power, avionics and software (PAS) advancements are needed to extend EVA capability on ISS beyond 2020, as well as future human space exploration missions. NASA is presently developing a space suit system called the Advanced Extravehicular Mobility Unit (AEMU). The AEMU PAS system is responsible for power supply and distribution for the overall EVA system, collecting and transferring several types of data to and from other mission assets, providing avionics hardware to perform numerous data display and in-suit processing functions, and furnishing information systems to supply data to enable crew members to perform their tasks with autonomy and efficiency. Current space suits are equipped with radio transmitters/receivers so that spacewalking astronauts can talk with ground controllers and/or other astronauts. The astronauts wear headsets with microphones and earphones. The transmitters/receivers are located in the backpacks worn by the astronauts only operate in the UHF band.

While a sufficient amount of radiation hardened electronics are available in areas such as serial processors, digital memory and Field Programmable Gate Arrays, certain ancillary electronic devices present a significant risk for the development of rad-hard spacesuit avionics. NASA is, therefore, seeking flight rated electronic devices needed to complement the existing inventory of flight rated parts so as to enable the creation of an advanced avionics suite for spacesuits. The suit and its corresponding avionics should be capable of being stowed inside a spacecraft outside the low-Earth orbit (LEO) environment for periods of up to 5 years (TBR). Devices should also be capable of supporting EVA sorties of at least 8 hours and total lifetime operational durations of at least 2300 hours (TBR) for a Mars surface mission. Assumptions may be made for inherent radiation shielding provided by the primary life-support system (PLSS) and possibly the power, avionics, and software (PAS) subsystem enclosure, but proposers are welcome to include shielding technologies at the board and individual part level to reduce the radiation requirements of the actual device. Devices should be immune to single event latch-up (SEL) for particles with Linear Energy Transfer (LET) values of at least 75 Mev-cm²/mg. and maintain full functionality for total ionizing doses of at least 20 Krad (Si). Criticality 1 devices (life support) must be fully mitigated against single event errors (SEE) for all potential mission radiation environments, including solar flares. Lower criticality devices can be less tolerant of SEEs, but must still operate with acceptable error rates in all potential radiation environments. Power consumption should be no more than 2X similar COTS or mil-spec devices. Devices should be vacuum compatible and need to support conduction cooling. Need currently exists for a number of devices, as described below. However this list should not be considered to be exhaustive and proposals will be considered for other devices that are peculiar to a spacesuit avionics suite. Additionally, proposals are invited for simplified, low-cost and low-impact methods to adapt or test commercial or military-spec devices so as to yield a flight-rated part to the above levels. In order of priority, two key innovations are sought this round:

- *Safety Critical Switches and Controls* - Very low profile switches and controls for EVA Criticality 1 systems. Highly reliable and robust devices that provide traditional toggle switch, rotary dial, and linear slider control functionality in a very low profile package which permits higher packaging density compared to traditional

solutions for vacuum space operations. Switches and controls must still be sized for easy operation with EVA gloves.

- *Wireless Communication* - Dual-band WLAN-class RF front-end module capable of supporting the SSCS (410 to 420 MHz) and the ISS External Wireless Communications system (5.25-5.35GHz). This module is expected to contain all RF components plus data converters. This module will interface with a baseband processing unit via high-speed digital interface. Consideration for supporting multiple antennas on the EWC band will be given, but this is not required. The front-end must be able to operate in the ISS environment.

Research done in Phase I of these efforts should focus on technical feasibility with an emphasis on hardware development that can be further expanded in a future Phase II award cycle. Phase II products must include a demonstration unit suitable for testing by NASA. Prototyping should be tailored to applications to ongoing HEO Mission Directorate missions and possible collaborative use in both the governmental and commercial manned spaceflight disciplines. Minimum deliverables at the end of Phase I are analysis and/or test reports, with priority given to functional hardware prototypes for further evaluation. Technical maturation plans should be submitted with Phase I submittals, as well as any expected commercial applications both internal and external to the manned spaceflight enterprise.