



## **NASA SBIR 2018 Phase I Solicitation**

### **Z11.01 NDE Sensors**

**Lead Center: LaRC**

**Participating Center(s): ARC, JSC**

**Technology Area: TA8 Science Instruments, Observatories & Sensor Systems**

Technologies sought under this SBIR program can be defined as advanced sensors, sensor systems, sensor techniques or software that enhance or expand NASA's current sensor capability. It is desirable but not necessary to target structural components of space flight hardware. Examples of space flight hardware will include light weight structural materials including composites and thin metals. Technologies sought include modular, smart, advanced Nondestructive Evaluation (NDE) sensor systems and associated capture and analysis software. It is advantageous for techniques to include the development on quantum, meta- and nano sensor technologies for deployment. Technologies enabling the ability to perform inspections on large complex structures will be encouraged. Technologies should provide reliable assessments of the location and extent of damage. Methods are desired to perform inspections in areas with difficult access in pressurized habitable compartments and external environments for flight hardware. Many applications require the ability to see through assembled conductive and/or thermal insulating materials without contacting the surface. Techniques that can dynamically and accurately determine position and orientation of the NDE sensor are needed to automatically register NDE results to precise locations on the structure. Advanced processing and displays are needed to reduce the complexity of operations for astronaut crews who need to make important assessments quickly. NDE inspection sensors are needed for potential use on free-flying inspection platforms. Integration of wireless systems with NDE may be of significant utility. It is strongly encouraged to provide explanation of how proposed techniques and sensors will be applied to a complex structure. Examples of structural components include but are not limited to multi-wall pressure vessels, batteries, tile, thermal blankets, micrometeoroid shielding, International Space Station (ISS) Radiators or aerospace structural components.

Phase I Deliverables - Lab prototype, feasibility study or software package including applicable data or observation of a measurable phenomenon on which the prototype will be built. Inclusion of a proposed approach to develop a given methodology to Technology Readiness Level (TRL) of 2-4. All Phase I's will include minimum of short description for Phase II prototype. It will be highly favorable to include description of how the Phase II prototype or methodology will be applied to structures.

Phase II Deliverables - Working prototype or software of proposed product, along with full report of development and test results. Prototype or software of proposed product should be of Technology Readiness Level (TRL 5-6). Proposal should include plan of how to apply prototype or software on applicable structure or material system. Opportunities and plans should also be identified and summarized for potential commercialization.

For proposers with an interest in airframes, please see Subtopic A1.01 - Structural Efficiency - Tailored Airframes and Structures.

