



## NASA SBIR 2018 Phase I Solicitation

### S1.05 Detector Technologies for UV, X-Ray, Gamma-Ray and Cosmic-Ray Instruments

Lead Center: JPL

Participating Center(s): GSFC, MSFC

Technology Area: TA8 Science Instruments, Observatories & Sensor Systems

This subtopic covers detector requirements for a broad range of wavelengths from UV through to gamma ray for applications in Astrophysics, Earth Science, Heliophysics, and Planetary Science. Requirements across the board are for greater numbers of readout pixels, lower power, faster readout rates, greater quantum efficiency, and enhanced energy resolution.

The proposed efforts must be directly linked to a requirement for a NASA mission. These include Explorers, Discovery, Cosmic Origins, Physics of the Cosmos, Solar-Terrestrial Probes, Vision Missions, and Earth Science Decadal Survey missions. Details of these can be found at the following URLs:

- General Information on Future NASA Missions - (<http://www.nasa.gov/missions>).
- Future planetary programs - (<https://solarsystem.nasa.gov/2013decadal/>).
- Earth Science Decadal missions - (<http://www.nap.edu/catalog/11820.html>).
- Helio Probes - (<http://solarsystem.nasa.gov/2013decadal/>).
  - [https://solar-orbiter.cnes.fr/en/SOLO/GP\\_spice.htm](https://solar-orbiter.cnes.fr/en/SOLO/GP_spice.htm).
  - <http://foxsi.ssl.berkeley.edu/>.
- X-ray Astrophysics - ([http://sites.nationalacademies.org/bpa/BPA\\_049810](http://sites.nationalacademies.org/bpa/BPA_049810)).
  - <http://wwwastro.msfc.nasa.gov/xrs/>.
  - <http://x-ifu.irap.omp.eu/>.

Specific technology areas are:

- Significant improvement in wide band gap semiconductor materials, such as AlGaIn, ZnMgO and SiC, individual detectors, and detector arrays for operation at room temperature or higher for missions such as GEO-CAPE, NWO, ATLAST and planetary science composition measurements.
- Highly integrated, low noise (< 300 electrons rms with interconnects), low power (< 100 uW/channel) mixed signal ASIC readout electronics as well as charge amplifier ASIC readouts with tunable capacitive inputs to match detector pixel capacitance. See needs of National Research Council's Earth Science Decadal Survey (NRC, 2007): Future Missions include GEO-CAPE, HypSIPI, GACM, future GOES and SOHO programs and planetary science composition measurements.
- Visible-blind SiC Avalanche Photodiodes (APDs) for EUV photon counting are required. The APDs must show a linear mode gain >10E6 at a breakdown reverse voltage between 80 and 100V. The APD's must demonstrate detection capability of better than 6 photons/pixel/s down to 135nm wavelength. See needs of National Research Council's Earth Science Decadal Survey (NRC, 2007): Tropospheric ozone.

- 
- Visible-blind UV and EUV detectors with small ( $< 10 \mu\text{m}$ ) pixels, large format, photon-counting sensitivity and detectivity, low voltage and power requirements, and room-temperature operation suitable for mission concepts such as the EUV Spectrograph on the ESA-NASA Solar Orbiter.
  - Large area ( $3 \text{ m}^2$ ) photon counting near-UV detectors with  $3 \text{ mm}$  pixels and able to count at  $10 \text{ MHz}$ . Array with high active area fraction ( $>85\%$ ),  $0.5$  megapixels and readout less than  $1 \text{ mW/channel}$ . Future instruments are focal planes for JEM-EUSO and OWL ultra-high energy cosmic ray instruments and ground Cherenkov telescope arrays such as CTA, and ring-imaging Cherenkov detectors for cosmic ray instruments such as BESS-ISO. As an example, (JEM-EUSO and OWL), imaging from low-Earth orbit of air fluorescence, UV light generated by giant air showers by ultra-high energy ( $E > 10^{19} \text{ eV}$ ) cosmic rays require the development of high sensitivity and efficiency detection of  $300\text{-}400 \text{ nm}$  UV photons to measure signals at the few photon (single photo-electron) level. A secondary goal minimizes the sensitivity to photons with a wavelength greater than  $400 \text{ nm}$ . High electronic gain ( $10^4$  to  $10^6$ ), low noise, fast time response ( $<10 \text{ ns}$ ), minimal dead time ( $<5\%$  dead time at  $10 \text{ ns}$  response time), high segmentation with low dead area ( $<20\%$  nominal,  $<5\%$  goal), and the ability to tailor pixel size to match that dictated by the imaging optics. Optical designs under consideration dictate a pixel size ranging from approximately  $2 \times 2 \text{ mm}^2$  to  $10 \times 10 \text{ mm}^2$ . Focal plane mass must be minimized ( $2 \text{ g/cm}^2$  goal). Individual pixel readout is required. The entire focal plane detector can be formed from smaller, individual sub-arrays.
  - Neutral density filter for hard x-rays ( $> 1 \text{ keV}$ ) to provide attenuation by a factor of  $10$  to  $1000$  or more. The filter must provide broad attenuation across a broad energy range (from  $1 \text{ keV}$  to  $\sim 100 \text{ keV}$  or more) with a flat attenuation profile of better than  $20\%$ .
  - Solar X-ray detectors with small independent pixels ( $< 250 \mu\text{m}$ ) and fast read-out ( $>10,000 \text{ count/s/pixel}$ ) over an energy range from  $< 5 \text{ keV}$  to  $300 \text{ keV}$ .
  - Proposals that address the development of supporting technologies that would help enable X-ray Surveyor mission that requires the development of X-ray microcalorimeter arrays with much larger field of view,  $\sim 10^5\text{-}10^6$  pixels, of pitch  $\sim 25\text{-}100 \mu\text{m}$ , and ways to read out the signals. For example, modular superconducting magnetic shielding is sought that can be extended to enclose a full scale focal plane array. All joints between segments of the shielding enclosure must also be superconducting.
  - For missions such as ATHENA X-IFU and X-ray Surveyor, improved long-wavelength blocking filters are needed for large-area, x-ray microcalorimeters. Filters with supporting grids are sought that, in addition to increasing filter strength, also enhance EMI shielding ( $1 - 10 \text{ GHz}$ ) and thermal uniformity for decontamination heating. X-ray transmission of greater than  $80\%$  at  $600 \text{ eV}$  per filter is sought, with infrared transmissions less than  $0.01\%$  and ultraviolet transmission of less than  $5\%$  per filter. Means of producing filter diameters as large as  $10 \text{ cm}$  should be considered.